Fire Net
WE SAVE LIVES
CEASE FIRE SOLUTIONS

PRODUCT DATASHEET

www.firenet.co.in · sales@firenet.co.in



FOAM (AFFF)

Foam Fire Extinguisher

9 L

- ISI marked · IS 15683
- 5-year warranty
- Fire classes: A and B
- Oils, paints, thinners and fuels

A Wood, paper, cloth **B** Oil, petrol, paint

TECHNICAL SPECIFICATIONS

GENERAL	
Capacity	9 L
Type	Portable, stored pressure (dry nitrogen)
Extinguishing agent	AFFF foam, 3 % / 6 % solution
Expelling agent	Nitrogen (stored pressure)
Fire classes	A and B
Fire rating	4A:144B
IS standard	IS 15683
Approvals	BIS (ISI mark)
Warranty	5 years
PERFORMANCE	
Working pressure	15 bar (at 27 °C)
Max service pressure	17 bar
Test pressure	30 bar (hydrostatic)
Burst pressure (body)	55 bar
Discharge time	15–30 sec
Discharge	97% (approx.)

PERFORMANCE	
Throw range	3–6 m
Operating temperature	+5 to +60 °C
BUILD	
Body	Red epoxy powder coat (RAL 3000), polymer lining inside
Sheet thickness	2.0 mm
Siphon tube	Plastic
Pressure gauge	Yes
Finish	Red epoxy powder coat (RAL 3000)
SIZE & WEIGHT	
Height	575 mm (approx.)
Diameter	180 ± 10 mm
Weight when full	14.0 kg (approx.)
Empty weight	4.3 kg
Carton size	210 × 210 × 630 mm
IN THE BOX	
In the box	Wall bracket with screws (powder-coated mild steel)
SERVICE	
Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.

FIRENET · Fire safety products & services, Pune

Call 75664 99966 / 75664 99977 / 75664 99988 / 75664 99911 · sales@firenet.co.in · www.firenet.co.in

Typical values; the rating and approvals printed on the product label apply. Specifications may change without notice. Issued Sep 2026.