

KITCHEN (K-TYPE)

Kitchen Fire Extinguisher (K-Type, SS Body)

9 L

- ISI marked · IS 15683 (K-Class)
- 5-year warranty
- Fire classes: K (cooking oil and fat) and A
- Stainless steel · commercial kitchens

A Wood, paper, cloth **K** Cooking oil

TECHNICAL SPECIFICATIONS

GENERAL	
Capacity	9 L
Type	Portable, stored pressure
Extinguishing agent	Wet chemical
Expelling agent	Nitrogen (UHP grade)
Fire classes	K (cooking oil and fat) and A
Fire rating	50F
IS standard	IS 15683 (K-Class)
Approvals	BIS (ISI mark)
Warranty	5 years
PERFORMANCE	
Working pressure	9 bar
Max service pressure	15 bar
Test pressure	35 bar
Burst pressure (body)	55 bar
Discharge time	30 sec
Discharge	95%
Operating temperature	+5 to +55 °C

BUILD	
Body	Stainless steel
Sheet thickness	1 mm
Valve	Brass
Hose / nozzle	Rubber braided EPDM hose
Siphon tube	SS
Pressure gauge	Yes (brass)
Finish	Smooth finish
SIZE & WEIGHT	
Height	620 mm
Diameter	180 ± 10 mm
Weight when full	13.5 kg
Empty weight	4.5 kg
Shipping weight	14.0 kg
IN THE BOX	
In the box	Wall bracket with screws (powder-coated mild steel)
SERVICE	
Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.

Typical values; the rating and approvals printed on the product label apply. Specifications may change without notice. Issued Sep 2026.