

AUTOMATIC / MODULAR

Modular Fire Extinguisher (Clean Agent, SS Body)

10 kg

- 5-year warranty
- Automatic · stainless steel

TECHNICAL SPECIFICATIONS

GENERAL	
Capacity	10 kg
Type	Automatic, ceiling-mounted modular unit
Extinguishing agent	Clean agent
Expelling agent	Nitrogen (UHP grade)
Warranty	5 years
PERFORMANCE	
Working pressure	15 bar
Test pressure	35 bar
Discharge time	10–15 sec (approx.)
Discharge	95%
Operating temperature	-30 to +60 °C

PERFORMANCE	
Volume protected	10 m^3 (approx.)
Area protected	4–5 m^2
Hanging height	1.75–2.25 m
BUILD	
Body	Stainless steel
SIZE & WEIGHT	
Diameter	300 ± 10 mm
Weight when full	14.11 kg
Empty weight	4.11 kg
Shipping weight	14.5 kg
IN THE BOX	
In the box	Ceiling mounting stand

How it works

1. Works on its own: when the heat below reaches the set temperature, the glass bulb bursts and the unit discharges
2. Mount it above the risk it protects, at the height shown in the specifications
3. No one needs to be present

Care & service

Check the gauge (where fitted), mounting and expiry date regularly and keep the area below clear. Replace or recharge the unit after it goes off.

Typical values; the rating and approvals printed on the product label apply. Specifications may change without notice. Issued Sep 2026.