Fire Net
WE SAVE LIVES
CEASE FIRE SOLUTIONS

PRODUCT DATASHEET

www.firenet.co.in · sales@firenet.co.in



WATER & WATER MIST

Water Fire Extinguisher

9 L

- ISI marked · IS 15683
- 5-year warranty
- Fire classes: A
- Wood, paper, cloth, cardboard

A Wood, paper, cloth

TECHNICAL SPECIFICATIONS

GENERAL	
Capacity	9 L
Type	Portable, stored pressure
Extinguishing agent	Water
Expelling agent	Nitrogen (UHP grade)
Fire classes	A
Fire rating	3A
IS standard	IS 15683
Approvals	BIS (ISI mark)
Warranty	5 years
PERFORMANCE	
Working pressure	15 bar
Max service pressure	18 bar
Test pressure	35 bar
Burst pressure (body)	55 bar
Discharge time	35 sec (approx.)
Discharge	97% (approx.)
Throw range	4–6 m
Operating temperature	+5 to +60 °C

BUILD	
Body	Mild steel sheet, max. 0.25% C, 0.05% P, 0.05% S (IS 513)
Sheet thickness	2.0 mm (top) / 2.5 (bottom)
Valve	Brass, M30×1.5 male thread
Hose / nozzle	Rubber braided EPDM hose (Burst pressure ≥ 55 bar)
Siphon tube	PVC / Plastic
Pressure gauge	Yes
Finish	PO Red as per IS 5 (Shade 538)
SIZE & WEIGHT	
Height	575 mm (approx.)
Diameter	180 ± 5 mm
Weight when full	13.9 kg (approx.)
Empty weight	5.0 kg
Shipping weight	14.5 kg
Carton size	210 × 210 × 630 mm
IN THE BOX	
In the box	Wall mounting bracket with screw
SERVICE	
Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.

Typical values; the rating and approvals printed on the product label apply. Specifications may change without notice. Issued Sep 2026.